



Commercial Solution Series

CST-2120

Public Address System
Transformer Module
Quick Start Guide

公共广播系统音频变压器
快速使用指南



Introduction

The amplifier JBL® part number CST-2120 is a 2-channel stereo amplifier designed to drive two 70V or 100V distributed audio systems.

The amplifier CSA-2120 is a 2-channel stereo amplifier designed to drive two 70V or 100V distributed audio systems.

- Rated to handle a maximum of 200W per channel.
- Rated for 70V and 100V distributed audio systems.
- The CSA-2120 amplifier is designed to drive two 70V or 100V distributed audio systems.
- Deactivates the amplifier when the power source is disconnected.

Installation

CAUTION: Before you begin, make sure that the amplifier is disconnected from the power source and all level controls are turned completely down (counter-clockwise).

1. If the amplifier is to be installed in a rack, use a 19-inch (48.3-cm) wide rack (EIA RS-310B) with a minimum depth of 4.5 inches (11.4 cm):
 - Rack the amplifier in the rack (See Figure A).
 - Rack the amplifier in the rack (See Figure B).
 - Wall mount the amplifier (See Figure C).
2. Connect the amplifier to the distributed audio system using the 4-conductor cable.
3. Disconnect the amplifier from the power source before connecting it to the distributed audio system.

Note: The CST-2120 amplifier is designed to drive two channels of a 70V or 100V distributed audio system. The amplifier is not designed to drive a single channel of a 70V or 100V distributed audio system. If you are using a single channel of a 70V or 100V distributed audio system, use the amplifier in a stereo configuration.

Specification

安装

1.

EI A RS-310B

19

- CSA-2120

A

-

B

-

C

2

4

3.

CSA-2120
CSA-2120

规格

部 件 名						